



HP Large Format 5000 & 5500 (Inkjet Printing)

Maximum Image Area Including Bleed

59 inches x variable length.

Resolution

High resolution 600 dpi CMYK

6-color/LC/LM

Substrates

Matte Paper

Glossy Paper

Backlit

Clear

Adhesive Vinyl

Scrim Vinyl

and more. Please ask your Account Executive.

GENERAL

- Your disk should include: only file(s) you would like printed, imported artwork (if any) and fonts. (Type 1 fonts must have both printer and screen components.)
- Files should be prepared in proportion to the final output size. The enlargement or reduction percentage must be written on the job order.
- Remember to include hard copy of the file(s) you are having output.
- Please specify the paper surface (paper or vinyl) on your work order.
- Please be sure that final files are in the CMYK color space.

SCANNED IMAGES

- Images should be scanned without any compensation for dot gain - as there is none.
- For best results, reproduction scans should be 300 dpi at final sizes up to



- 20 x 24. A minimum of 200 dpi is suggested for sizes up to 30 x 36; 150 dpi for anything larger.
- All images must be in the CMYK color space and saved as TIFF or EPS files.

PHOTOSHOP

- Photoshop EPS files should be in the CMYK color space and saved with binary encoding and an 8-bit preview.
- Photoshop TIFF files should be in the CMYK space and saved *WITHOUT* alpha channels or LZW compression.
- Clipping path flatness should be set between 2 and 5.

ILLUSTRATOR ARTWORK

- All artwork must be saved as EPS files.
- EPS artwork must be imported into a page layout application, preferably QuarkXPress. DO NOT set up pages as spreads.
- Include NO colorized TIFF files or DCS files.